



8,000 BHP ANCHOR HANDLING TUG SUPPLY VESSEL

MAIN CHARACTERISTICS

HULL

Length Overall	74.50 M
Length BP	65.00 M
Breadth Moulded	18.00 M
Depth Moulded	8.00 M
Design Draft	5.50 M
Gross Tonnage	10.0 T/M ²
Max Speed	14 Knots @ 100% MCR
Bollard Pull	100 MT @ 100% MCR
Complement	36 POB

CLASSIFICATION

AMERICAN BUREAU OF SHIPPING

ABS: ✕ A1, (E), Offshore Support Vessel (AH, Supply, Tow, FFV1), SPS, ✕ AMS, ✕ DPS-2,
✕ ACCU, UNWILD

REFERENCES

KT213 (2021) – HULL T8008

PaxOcean Engineering Pte Ltd

1 Kim Seng Promenade, #06-02 Great World City, Singapore 237994, Tel: +65 6733 3500 ♣ Fax: +65 6836 1642 ♣ marketing@paxocean.com ♣ www.paxocean.com

Note: The information and sketches in this document are given in good faith without express, implied or statutory warranty or condition. All information contained in or disclosed by this drawing/document is confidential and proprietary, and is the exclusive intellectual property of PaxOcean Engineering Pte Ltd. All further design, use and sales rights attached thereto are exclusively reserved by PaxOcean Engineering Pte Ltd. Any reproduction, communication or distribution of this information is prohibited without the prior written consent of PaxOcean Engineering Pte Ltd.

PaxOcean